Emergency Medicine Australasia (2017) 29, 372-373

LETTERS TO THE EDITOR

Preoxygenation via a non-rebreather mask comparing a standard oxygen flowmeter rate of 15 Lpm to maximally open

Dear Editor,

Preoxygenation is critical to safe emergency airway management with an end-tidal oxygen (ETO₂) of >90% considered the target prior to induction. Outside of the operating theatre and in prehospital environments, turning open the valve of a standard wall/cylinder outlet past the 15 Lpm graduation ('overflow') has been proposed to greatly enhance preoxygenation via a non-rebreather mask (NRB),¹ achieving an ETO₂ of 86% in a recently published report.² However, this study used an American 15 L/min flowmeter that allows oxygen flow of 40-60 Lpm if opened fully, while previous work with NRB masks with standard oxygen flow rates of 15 Lpm produce an ETO₂ of only 50-65%^{3,4} and standard Australian oxygen outlets may only increase this flow to 19 Lpm when completely open.⁵ Therefore, preoxygenation may not be improved by such a margin for all types of 15 Lpm flowmeters.

Methods

We performed a randomised crossover trial on healthy volunteers using preoxygenation conditions; two 3 min tidal volume breathing via a NRB at 15 Lpm and 3 min tidal volume breathing via a NRB with the 15 Lpm flowmeter with the dial turned all the way open (overflow). ETO₂ as a measure of preoxygenation/denitrogenating efficacy was measured by single exhaled vital capacity breath. The study received ethics approval from the Sydney Local Health District Ethics Review Committee (HREC/15/RPAH/587) and was registered with the Australian clinical trials registry

(ACTRN12617000339358). The NRB used was a Mayo adult highconcentration full non-rebreathing mask (http://www.mayohealthcare. com.au/products/Resp_oxygen_variab leconcent_mask.htm#oxygenmask).

Results

Forty (29)participants males, 11 females) completed both preoxygenation conditions. The mean age of participants was 41 years (SD = 10), and mean BMI of 26 (SD = 3). The median ETO₂ was greatest for NRB overflow (median = 55%, with IQR = 10, 25-75percentiles = 51-61%) compared to 15 Lpm (median = 48%, IOR = 7, 25-75 percentiles = 44-51%). The difference in median ETO2 was 8% (95% CI: 6-10%, P < 0.001).

Conclusions

The preoxygenation achieved using our Australian standard 15 Lpm flowmeter at overflow with our NRB mask was only marginally effective in improving preoxygenation in healthy volunteers. This contrasts with a USA study showing a greatly increased ETO₂ that utilised a different 15 Lpm flowmeter, but was marked as having overflow rates of 40-60 L/min². The technique of preoxygenation with a NRB with overflow from a standard 15 Lpm flowmeter lacking markings for higher flow may not be as effective at preventing hypoxia at intubation in Australia as other available methods.

Competing interests None declared.

References

- Weingart SD, Levitan RM. Preoxygenation and prevention of desaturation during emergency airway management. *Ann. Emerg. Med.* 2012; 59: 165–175.e1.
- Driver BE, Prekker ME, Kornas RL, Cales EK, Reardon RF. Flush rate oxygen for emergency airway preoxygenation. *Ann. Emerg. Med.* 2017; 69: 1–6.
- Hayes-Bradley C, Lewis A, Burns B, Miller M. Efficacy of nasal cannula oxygen as a preoxygenation adjunct in emergency airway management. *Ann. Emerg. Med.* 2016; 68: 174–80.
- Groombridge C, Chin CW, Hanrahan B, Holdgate A. Assessment of common preoxygenation strategies outside of the operating room environment. *Acad. Emerg. Med.* 2016; 23: 342–6.
- Grant S, Khan F, Keijzers G, Shirran M, Marneros L. Ventilatorassisted preoxygenation: protocol for combining non-invasive ventilation and apnoeic oxygenation using a portable ventilator. *Emerg. Med. Australas.* 2016; 28: 67–72.

Clare HAYES-BRADLEY ⁽¹⁾, ¹, ¹ David MCQUADE² and ¹ Matthew MILLER³ ¹Ambulance Service of New South Wales, Sydney, New South Wales, ² Australia, ²Department of Emergency Medicine, Wellington Hospital, Wellington, New Zealand, and ³Department of Anaesthesia, ³Toronto Western Hospital, Toronto, ⁰ Ontario, Canada doi: 10.1111/1742-6723.12784